






OMEGA
AIR

ALTERNATIVE FILTER ELEMENTS

FIAC

	Q	P	D	C
FIAC Plastic end caps				
Particle retention	3 µm	0,1 µm	0,01 µm	activated carbon
Solids - q. class (ISO 8573-1)	6	2	1	1*
Oils - q. class (ISO 8573-1)	-	2	1	1
Filter media	acrylic fibres, cellulose	borosilicate micro fibres		activated carbon
Operating temp. range [°C]	1,5 to 65	1,5 to 65	1,5 to 65	1,5 to 45
Diff. pressure (new) [mbar]	10	50	80	60

	Q		P		D		C	
	FIAC	OMEGA AIR	FIAC	OMEGA AIR	FIAC	OMEGA AIR	FIAC	OMEGA AIR
	FQ 1000	OFC 1000 Q/P	FP 1000	OFC 1000 P/M	FD 1000	OFC 1000 D/S	FC 1000	OFC 1000 C/A
	FQ 1300	OFC 1300 Q/P	FP 1300	OFC 1300 P/M	FD 1300	OFC 1300 D/S	FC 1300	OFC 1300 C/A
	FQ 2000	OFC 2000 Q/P	FP 2000	OFC 2000 P/M	FD 2000	OFC 2000 D/S	FC 2000	OFC 2000 C/A
	FQ 3300	OFC 3300 Q/P	FP 3300	OFC 3300 P/M	FD 3300	OFC 3300 D/S	FC 3300	OFC 3300 C/A
	FQ 5600	OFC 5600 Q/P	FP 5600	OFC 5600 P/M	FD 5600	OFC 5600 D/S	FC 5600	OFC 5600 C/A
	FQ 8600	OFC 8500 Q/P	FP 8600	OFC 8500 P/M	FD 8600	OFC 8500 D/S	FC 8600	OFC 8500 C/A
	FQ 13000	OFC 13000 Q/P	FP 13000	OFC 13000 P/M	FD 13000	OFC 13000 D/S	FC 13000	OFC 13000 C/A
	FQ 16500	OFC 16500 Q/P	FP 16500	OFC 16500 P/M	FD 16500	OFC 16500 D/S	FC 16500	OFC 16500 C/A
	FQ 25000	OFC 25000 Q/P	FP 25000	OFC 25000 P/M	FD 25000	OFC 25000 D/S	FC 25000	OFC 25000 C/A

* Valid if "S" filter cartridge is installed upstream.