




**OMEGA** **ALTERNATIVE**  
**AIR** **FILTER ELEMENTS**

**SCHNEIDER**

	VP	FP	AP
<b>SCHNEIDER</b>  Plastic end caps			
Particle retention	<b>3 µm</b>	<b>0,01 µm</b>	<b>activated carbon</b>
Solids - q. class (ISO 8573-1)	6	1	1*
Oils -q. class (ISO 8573-1)	-	1	1
Filter media	acrylic fibres, cellulose		activated carbon
Operating temp. range [°C]	1,5 to 65	1,5 to 65	1,5 to 45
Diff. pressure (new) [mbar]	10	80	60

	VP		FP		AP	
	SCHNEIDER	OMEGA AIR	SCHNEIDER	OMEGA AIR	SCHNEIDER	OMEGA AIR
	<b>F-VP 6</b>	OSC 6 VP/P	<b>F-FP 6</b>	OSC 6 FP/S	<b>F-AP 6</b>	OSC 6 AP/A
	<b>F-VP 10</b>	OSC 10 VP/P	<b>F-FP 10</b>	OSC 10 FP/S	<b>F-AP 10</b>	OSC 10 AP/A
	<b>F-VP 15</b>	OSC 15 VP/P	<b>F-FP 15</b>	OSC 15 FP/S	<b>F-AP 15</b>	OSC 15 AP/A
	<b>F-VP 30</b>	OSC 30 VP/P	<b>F-FP 30</b>	OSC 30 FP/S	<b>F-AP 30</b>	OSC 30 AP/A
	<b>F-VP 45</b>	OSC 45 VP/P	<b>F-FP 45</b>	OSC 45 FP/S	<b>F-AP 45</b>	OSC 45 AP/A
	<b>F-VP 80</b>	OSC 80 VP/P	<b>F-FP 80</b>	OSC 80 FP/S	<b>F-AP 80</b>	OSC 80 AP/A

\* Valid if "S" filter cartridge is installed upstream.