

**NEREZ****Spojky STORZ**

z nerezové oceli



Spojky s vnitřním závitem					
Obj. č.	Typ spojky	Závít	Tlak (bar)	Rozměr bajonetu	Materiál
STI-2512SS	D/25	G 1/2"	16	31	nerez
STI-2534SS	D/25	G 3/4"	16	31	nerez
STI-2510SS	D/25	G 1"	16	31	nerez
STI-5210SS	C/52	G 1"	16	66	nerez
STI-5254SS	C/52	G 1 1/4"	16	66	nerez
STI-5215SS	C/52	G 1 1/2"	16	66	nerez
STI-5220SS	C/52	G 2"	16	66	nerez
STI-5225SS	C/52	G 2 1/2"	16	66	nerez
STI-6520SS	65	G 2"	16	81	nerez
STI-6525SS	65	G 2 1/2"	16	81	nerez
STI-7520SS	B/75	G 2"	16	89	nerez
STI-7525SS	B/75	G 2 1/2"	16	89	nerez
STI-7530SS	B/75	G 3"	16	89	nerez
STI-10040SS	100	G 4"	16	115	nerez
STI-11040SS	A/110	G 4"	16	133	nerez
STI-11045SS	A/110	G 4 1/2"	16	133	nerez

Redukované spojky						
Obj. č.	Typ spojky 1	Typ spojky 2	Tlak (bar)	Rozměr bajonetu 1	Rozměr bajonetu 2	Materiál
STR-5225SS	C/52	D/25	16	66	31	nerez
STR-6552SS	65	C/52	16	81	66	nerez
STR-7552SS	B/75	C/52	16	89	66	nerez
STR-7565SS	B/75	65	16	89	81	nerez
STR-11075SS	A/110	B/75	16	133	89	nerez

Spojky s přírubou PN 16					
Obj. č.	Typ spojky	Světlost DN	Tlak (bar)	Rozměr bajonetu	Materiál
STF-2525SS	D/25	25	16	31	nerez
STF-5250SS	C/52	50	16	66	nerez
STF-6565SS	65	65	16	81	nerez
STF-7580SS	B/75	80	16	89	nerez
STF-110100SS	A/110	100	16	133	nerez

Zaslepovací spojky s řetízkem				
Obj. č.	Typ spojky	Tlak (bar)	Rozměr bajonetu	Materiál
STP-25SS	D/25	16	31	nerez
STP-52SS	C/52	16	66	nerez
STP-65SS	65	16	81	nerez
STP-75SS	B/75	16	89	nerez
STP-100SS	100	16	115	nerez
STP-110SS	A/110	16	133	nerez

**Náhradní těsnění pro spojky STORZ**

• teplotní odolnost: NBR -40/+110 °C, silikon -60/+180 °C, FKM -15/+200 °C, EPDM -35/+130 °C

Náhradní těsnění pro spojky Storz					
NBR	Obj. č.			Typ spojky	Rozměr bajonetu
	Silikon	FKM	EPDM		
STD-25N	STD-25S	STD-25V	-	D/25	31
STD-32N	STD-32S	-	-	32	44
STD-38N	STD-38S	STD-38V	-	38	52
STD-52N	STD-52S	STD-52V	STD-52E	C/52	66
STD-65N	STD-65S	STD-65V	-	65	81
STD-75N	STD-75S	STD-75V	STD-75E	B/75	89
STD-90N	STD-90S	-	-	90	105
STD-100N	STD-100S	STD-100V	-	100	115
STD-110N	STD-110S	STD-110V	STD-110E	A/110	133

