


Spojky pro betonové směsi MST

z temperované litiny/oceli

LÜDECKE




Vsvuky s vnitřním závitem						
Systém 22	Systém 23,5	Závít	Velikost	Rozměr	h	Hmotnost (g)
VIG10/25	-	G 1"	25	35	67	280
VIG10-X25	-	G 1"	X25	41	67	345
VIG54-X25	-	G 1 1/4"	X25	41	67	386
VIG10/35	VIG10/35-N	G 1"	35	49,5	63	521
VIG54/35	VIG54/35-N	G 1 1/4"	35	49,5	68	461
VIG15/35	VIG15/35-N	G 1 1/2"	35	49,5	68	453
VIG20/35	VIG20/35-N	G 2"	35	49,5	74	665
VIG15/42	-	G 1 1/2"	42	53	62	420
VIG54/50	VIG54/50-N	G 1 1/4"	50	63	64	820
VIG15/50	VIG15/50-N	G 1 1/2"	50	63	64	678
VIG20/50	VIG20/50-N	G 2"	50	63	71	620
VIG25/50	VIG25/50-N	G 2 1/2"	50	63	78	960
VIG25/65*	-	G 2 1/2"	65	73	78	999




Vsvuky s otočným vnitřním závitem						
Systém 22	Systém 23,5	Závít	Velikost	Rozměr	h	Hmotnost (g)
VIG10-X25-DR	-	G 1"	X25	41	106	610
VIG54/35-DR	VIG54/35-DR-N	G 1 1/4"	35	49,5	120	840
VIG20/50-DR	VIG20/50-DR-N	G 2"	50	63	130	1 040



Vsvuky s vnějším závitem						
Systém 22	Systém 23,5	Závít	Velikost	Rozměr	h	Hmotnost (g)
VAG10/25	-	G 1"	25	35	76	356
VAG10-X25	-	G 1"	X25	41	76	382
VAG54/35	VAG54/35-N	G 1 1/4"	35	49,5	83	527
VAG15/42	-	G 1 1/2"	42	53	77	525
VAG20/50	VAG20/50-N	G 2"	50	63	90	950



Redukované vsuvky – vsuvka / vsuvka							
Systém 22	Systém 23,5	Velikost 1	Rozměr 1	Velikost 2	Rozměr 2	h	Hmotnost (g)
VRX25/25	-	X25	41	25	35	90	448
VR35/25	VR35-N/25	35	49,5	25	35	97	654
VR35/X25	VR35-N/X25	35	49,5	X25	41	100	690
VR42/X25	-	42	53	X25	41	90	620
VR42/35	VR42/35-N	42	53	35	49,5	90	650
VR50/X25	VR50-N/X25	50	63	X25	41	100	955
VR50/35	VR50-N/35-N	50	63	35	49,5	100	955
VR50/42	VR50-N/42	50	63	42	53	95	983



* max. pracovní tlak pro velikost 65 je PN 25 bar