


Koncovky Global Spiral

se závity BSP


Kolena 90° s vnitřním závitem s kuzelem 60°, s o-kroužkem, otočná						
Obj. č.	Hadice D DN	Závít BSP	A (mm)	B (mm)	E (mm)	H (mm)
GG-F90-3810	10 mm	G 3/8"	78,0	42,2	32,0	22,0
GG-F90-1212	12 mm	G 1/2"	88,0	50,5	37,5	27,0
GG-F90-5816	16 mm	G 5/8"	112,5	62,2	46,0	30,0
GG-F90-3416	16 mm	G 3/4"	112,5	62,2	60,0	32,0
GG-F90-3420	20 mm	G 3/4"	126,0	75,0	60,0	32,0
GG-F90-1025	25 mm	G 1"	151,0	94,6	70,0	41,0
GG-F90-5432	32 mm	G 1 1/4"	180,5	109,4	80,0	50,0
GG-F90-1540	40 mm	G 1 1/2"	194,6	121,0	1 000	55,0
GG-F90-2050	50 mm	G 2"	254,7	162,7	129,1	70,0

Poznámka: pro rozměry 10 až 32 mm je pracovní tlak 420 bar



Koncovky s vnějším závitem s kuzelem 60°					
Obj. č.	Hadice D DN	Závít BSP	A (mm)	B (mm)	H (mm)
GG-M-3810	10 mm	G 3/8"	63,0	27,2	22,0
GG-M-1210	10 mm	G 1/2"	68,0	32,2	27,0
GG-M-1212	12 mm	G 1/2"	67,5	30,0	27,0
GG-M-5816	16 mm	G 5/8"	84,0	33,7	30,0
GG-M-3416	16 mm	G 3/4"	85,0	34,7	32,0
GG-M-3420	20 mm	G 3/4"	85,0	34,7	32,0
GG-M-1020	20 mm	G 1"	90,0	39,0	41,0
GG-M-1025	25 mm	G 1"	98,0	41,2	41,0
GG-M-5432	32 mm	G 1 1/4"	118,0	46,9	50,0
GG-M-1540	40 mm	G 1 1/2"	130,0	56,4	55,0
GG-M-2050	50 mm	G 2"	148,8	56,8	70,0

Poznámka: pro rozměry 10 až 32 mm je pracovní tlak 420 bar



související zboží:

Manometry
str. 625



Hydraulické trubky
str. 410



Rychlospojky
str. 407



Hadice
str. 342

