



## Koncovky Global Spiral

se závitů DIN 24°, lehká a těžká řada



Kolena 90°, těžká řada, s vnitřním závitem DIN 24°, s o-kroužkem, otočné						
Obj. č.	Hadice D DN	Závit M	A (mm)	B (mm)	E (mm)	H (mm)
GMH-F90-2010	10 mm	M20 × 1,5	78,0	42,2	37,0	24,0
GMH-F90-2210	10 mm	M22 × 1,5	78,0	42,2	40,0	27,0
GMH-F90-2412	12 mm	M24 × 1,5	88,0	50,5	44,0	30,0
GMH-F90-3016	16 mm	M30 × 2,0	112,5	62,2	51,0	36,0
GMH-F90-3020	20 mm	M30 × 2,0	126,0	75,0	62,0	36,0
GMH-F90-3620	20 mm	M36 × 2,0	126,0	75,0	64,0	46,0
GMH-F90-3625	25 mm	M36 × 2,0	151,0	94,6	76,0	46,0
GMH-F90-4225	25 mm	M42 × 2,0	151,0	94,6	76,0	50,0
GMH-F90-5232	32 mm	M52 × 2,0	180,5	109,4	87,0	60,0
GMH-F90-5240	40 mm	M52 × 2,0	194,6	121,0	92,0	60,0

Poznámka: pro rozměry 10 až 32 mm je pracovní tlak 420 bar



Koncovky DIN 24°, těžká řada, s vnějším závitem					
Obj. č.	Hadice D DN	Závit M	A (mm)	B (mm)	H (mm)
GMH-M-2010	10 mm	M20 × 1,5	63,7	27,9	22,0
GMH-M-2210	10 mm	M22 × 1,5	65,7	29,9	24,0
GMH-M-2412	12 mm	M24 × 1,5	67,5	30,0	27,0
GMH-M-3016	16 mm	M30 × 2,0	85,0	34,7	32,0
GMH-M-3020	20 mm	M30 × 2,0	85,0	34,0	32,0
GMH-M-3620	20 mm	M36 × 2,0	89,0	38,0	41,0
GMH-M-4220	20 mm	M42 × 2,0	95,0	44,0	46,0
GMH-M-3625	25 mm	M36 × 2,0	97,0	40,2	41,0
GMH-M-4225	25 mm	M42 × 2,0	99,0	42,2	46,0
GMH-M-5232	32 mm	M52 × 2,0	123,0	51,9	55,0

Poznámka: pro rozměry 10 až 32 mm je pracovní tlak 420 bar

### související zboží:

Hydraulická šroubení  
str. 412



Těsnění závitů  
str. 86



Hydraulické trubky  
str. 410



Manometry  
str. 625

