

Hydraulická šroubení

přímá šroubení

Přímá šroubení s vnějším trubkovým závitem, s měkkým těsněním										
Obj. č.		Řada	Tlak PN (bar)		Závít G	Trubka D	Délka L1	Dél. závitu i	SW S1	SW S
ocel	nerez		ocel	nerez						
AW-G186L	AWX-G186L	L	500	315	G 1/8"	6 mm	23	8	14	14
AW-G146L	AWX-G146L	L	500	315	G 1/4"	6 mm	25	12	14	19
AW-G188L	AWX-G188L	L	500	315	G 1/8"	8 mm	23	8	17	14
AW-G148L	AWX-G148L	L	500	315	G 1/4"	8 mm	25	12	17	19
AW-G388L	AWX-G388L	L	500	315	G 3/8"	8 mm	26	12	17	22
AW-G1410L	AWX-G1410L	L	500	315	G 1/4"	10 mm	26	12	19	19
AW-G3810L	AWX-G3810L	L	500	315	G 3/8"	10 mm	27	12	19	22
AW-G1210L	AWX-G1210L	L	500	315	G 1/2"	10 mm	28	14	19	27
AW-G1412L	AWX-G1412L	L	400	315	G 1/4"	12 mm	27	12	22	19
AW-G3812L	AWX-G3812L	L	400	315	G 3/8"	12 mm	27	12	22	22
AW-G1212L	AWX-G1212L	L	400	315	G 1/2"	12 mm	28	14	22	27
AW-G3815L	AWX-G3815L	L	400	315	G 3/8"	15 mm	29	12	27	24
AW-G1215L	AWX-G1215L	L	400	315	G 1/2"	15 mm	29	14	27	27
AW-G1218L	AWX-G1218L	L	400	315	G 1/2"	18 mm	31	14	32	27
AW-G3418L	AWX-G3418L	L	400	315	G 3/4"	18 mm	31	16	32	32
AW-G3422L	AWX-G3422L	L	250	160	G 3/4"	22 mm	33	16	36	32
AW-G1028L	AWX-G1028L	L	250	160	G 1"	28 mm	34	18	41	41
AW-G5435L	AWX-G5435L	L	250	160	G 1 1/4"	35 mm	39	20	50	50
AW-G1542L	AWX-G1542L	L	250	160	G 1 1/2"	42 mm	42	22	60	55
AW-G146S	AWX-G146S	S	800	630	G 1/4"	6 mm	28	12	17	19
AW-G148S	AWX-G148S	S	800	630	G 1/4"	8 mm	30	12	19	19
AW-G388S	AWX-G388S	S	800	630	G 3/8"	8 mm	30	12	19	22
AW-G1410S	AWX-G1410S	S	800	630	G 1/4"	10 mm	31	12	22	19
AW-G3810S	AWX-G3810S	S	800	630	G 3/8"	10 mm	31	12	22	22
AW-G1210S	AWX-G1210S	S	800	630	G 1/2"	10 mm	34	14	22	27
AW-G1412S	AWX-G1412S	S	630	630	G 1/4"	12 mm	33	12	24	22
AW-G3812S	AWX-G3812S	S	630	630	G 3/8"	12 mm	33	12	24	22
AW-G1212S	AWX-G1212S	S	630	630	G 1/2"	12 mm	34	14	24	27
AW-G1214S	AWX-G1214S	S	630	630	G 1/2"	14 mm	37	14	27	27
AW-G1216S	AWX-G1216S	S	630	400	G 1/2"	16 mm	37	14	30	27
AW-G3816S	AWX-G3816S	S	630	400	G 3/8"	16 mm	36	12	30	27
AW-G3416S	AWX-G3416S	S	630	400	G 3/4"	16 mm	39	16	30	32
AW-G3420S	AWX-G3420S	S	400	400	G 3/4"	20 mm	42	16	36	32
AW-G1225S	-	S	400	-	G 1/2"	25 mm	47	14	46	41
AW-G1025S	AWX-G1025S	S	400	400	G 1"	25 mm	47	18	46	41
AW-G5430S	AWX-G5430S	S	400	400	G 1 1/4"	30 mm	50	20	50	50
AW-G1538S	AWX-G1538S	S	400	315	G 1 1/2"	38 mm	57	22	60	55

Upozornění: pro objednání těla šroubení bez matice a rezného kroužku uveďte na začátek obj.č. písmeno X, například XAW-G146L.

související zboží:

Trubky
str. 410



Těsnění závitů
str. 86



Rychlospojky
str. 407



Hydraulické adaptéry
str. 388

