


Hydraulická šroubení

přímá šroubení

Přímá šroubení s vnějším UNF/UN závitem a těsnícím o-kroužkem									
Obj. č.		Řada	Tlak PN (bar)	Závit G	Trubka D	Délka L1	Dél. závitu i	SW S1	SW S
ocel	nerez								
A-U7168L	-	L	500	7/16-20 UNF	8 mm	25	9	17	17
A-U3412L	-	L	400	3/4-16 UNF	12 mm	28	11	22	24
A-U7812L	-	L	400	7/8-14 UNF	12 mm	29	12,7	22	27
A-U3415L	-	L	400	3/4-16 UNF	15 mm	29	11	27	24
A-U7815L	-	L	400	7/8-14 UNF	15 mm	30	12,7	27	27
A-U3418L	-	L	400	3/4-16 UNF	18 mm	31	11	32	27
A-U7818L	-	L	400	7/8-14 UNF	18 mm	31	12,7	32	27
A-U7822L	-	L	250	7/8-14 UNF	22 mm	33	12,7	36	32
A-U111622L	-	L	250	11/16-12 UN	22 mm	33	15	36	32
A-U151622L	-	L	250	15/16-12 UN	22 mm	34	15	36	41
A-U111628L	-	L	250	11/16-12 UN	28 mm	34	15	41	41
A-U151628L	-	L	250	15/16-12 UN	28 mm	34	15	41	41
A-U151635L	-	L	250	15/16-12 UN	35 mm	39	15	50	46
A-U15835L	-	L	250	15/8-12 UN	35 mm	39	15	50	50
A-U15842L	-	L	250	15/8-12 UN	42 mm	42	15	60	55
A-U7168S	-	S	800	7/16-20 UNF	8 mm	30	9	19	17
A-U91610S	-	S	800	9/16-18 UNF	10 mm	31	10	22	19
A-U91612S	-	S	630	9/16-18 UNF	12 mm	31	10	24	22
A-U3412S	-	S	630	3/4-16 UNF	12 mm	34	11	24	24
A-U3416S	-	S	630	3/4-16 UNF	16 mm	34	11	30	24
A-U7816S	-	S	630	7/8-14 UNF	16 mm	37	12,7	30	27
A-U3420S	-	S	400	3/4-16 UNF	20 mm	42	11	36	32
A-U7820S	-	S	400	7/8-14 UNF	20 mm	42	12,7	36	32
A-U111620S	-	S	400	11/16-12 UN	20 mm	42	15	36	32
A-U111625S	-	S	400	11/16-12 UN	25 mm	47	15	46	36
A-U151625S	-	S	400	15/16-12 UN	25 mm	47	15	46	41
A-U151630S	-	S	400	15/16-12 UN	30 mm	50	15	50	46
A-U15838S	-	S	400	15/8-12 UN	38 mm	57	15	60	55

Upozornění: pro objednání těla šroubení bez matice a rezného kroužku uveďte na začátek obj.č. písmeno X, např. XA-U7168L



3

související zboží:

Trubky
str. 410



Těsnění závitů
str. 86



Rychlospojky
str. 407



Hydraulické adaptéry
str. 388

