


Hydraulická šroubení

přímá šroubení

3



Redukovaná šroubení – těžká řada										
Obj. č.		Řada	Tlak PN (bar)		Trubka D2	Trubka D1	Závit d1	Délka L1	SW S1	SW S2
ocel	nerez		ocel	nerez						
R-68S	RX-68S	S	800	630	6 mm	8 mm	M16 × 1,5	25	17	19
R-610S	RX-610S	S	800	630	6 mm	10 mm	M18 × 1,5	25	17	22
R-810S	RX-810S	S	800	630	8 mm	10 mm	M18 × 1,5	25	19	22
R-812S	RX-812S	S	630	630	8 mm	12 mm	M20 × 1,5	26	19	24
R-1012S	RX-1012S	S	630	630	10 mm	12 mm	M20 × 1,5	27	22	24
R-1014S	RX-1014S	S	630	630	10 mm	14 mm	M22 × 1,5	27	22	27
R-1214S	RX-1214S	S	630	630	12 mm	14 mm	M22 × 1,5	27	24	27
R-616S	RX-616S	S	630	400	6 mm	16 mm	M24 × 1,5	26	17	30
R-816S	RX-816S	S	630	400	8 mm	16 mm	M24 × 1,5	26	19	30
R-1016S	RX-1016S	S	630	400	10 mm	16 mm	M24 × 1,5	27	22	30
R-1216S	RX-1216S	S	630	400	12 mm	16 mm	M24 × 1,5	27	24	30
R-1416S	-	S	630	-	14 mm	16 mm	M24 × 1,5	30	27	30
R-820S	-	S	400	-	8 mm	20 mm	M30 × 2	27	19	36
R-1020S	RX-1020S	S	400	400	10 mm	20 mm	M30 × 2	28	22	36
R-1220S	RX-1220S	S	400	400	12 mm	20 mm	M30 × 2	28	24	36
R-1620S	RX-1620S	S	400	400	16 mm	20 mm	M30 × 2	31	30	36
R-825S	-	S	400	-	8 mm	25 mm	M36 × 2	28	19	46
R-1225S	RX-1225S	S	400	400	12 mm	25 mm	M36 × 2	29	24	46
R-1625S	RX-1625S	S	400	400	16 mm	25 mm	M36 × 2	31	30	46
R-2025S	RX-2025S	S	400	400	20 mm	25 mm	M36 × 2	35	36	46
R-1230S	-	S	400	-	12 mm	30 mm	M42 × 2	28	24	50
R-1630S	RX-1630S	S	400	400	16 mm	30 mm	M42 × 2	31	30	50
R-2030S	RX-2030S	S	400	400	20 mm	30 mm	M42 × 2	35	36	50
R-2530S	-	S	400	-	25 mm	30 mm	M42 × 2	38	46	50
R-1638S	-	S	400	-	16 mm	38 mm	M52 × 2	31	30	60
R-2038S	RX-2038S	S	400	315	20 mm	38 mm	M52 × 2	35	36	60
R-2538S	RX-2538S	S	400	315	25 mm	38 mm	M52 × 2	38	46	60
R-3038S	RX-3038S	S	400	315	30 mm	38 mm	M52 × 2	41	50	60

Upozornění: pro objednání samostatného těla šroubení uveďte na začátek obj.č. písmeno X, např. XR-68S

související zboží:

Hadice
str. 342



Rychlospojky
str. 407



Nástrčné spojky
str. 38



Manometry
str. 625

