

VVG (objem 100 až 5000 l) tlakové nádoby

- ocelové provedení, galvanizované
- vyrobené dle směrnice PED 68/2014ES
- pro stlačený vzduch a dusík
- pracovní tlak 32 bar
- pracovní teplota -20/+50 °C



Obj. č.	Objem (l)	Tlak (bar)	Rozměry (mm)			Hmotnost (kg)
			De	L	A	
VVG100-32	100	32	370	1 213	180	89
VVG270-32	270	32	500	1 648	175	192
VVG500-32	500	32	600	2 050	155	308
VVG1000-32	1 000	32	800	2 350	145	470
VVG1500-32	1 500	32	1 000	2 305	170	665
VVG2000-32	2 000	32	1 000	2 740	170	1 100
VVG3000-32	3 000	32	1 200	2 990	140	1 535
VVG4000-32	4 000	32	1 450	2 790	225	1 950
VVG5000-32	5 000	32	1 450	3 390	225	2 280

Připojení

Obj. č.	1	2	3	4	5	6	7
VVG100-32	2"	3/4"	-	3/8"	3/8"	-	3/4"
VVG270-32	2"	1"	1"	-	3/8"	1"	1"
VVG500-32	2"	2"	2"	1/2"	1/2"	2"	2"
VVG1000-32	2"	2"	2"	3/8"	3/8"	2"	2"
VVG1500-32	2"	2"	2"	1/2"	1/2"	2"	2"
VVG2000-32	2"	2"	2"	1/2"	1/2"	2"	2"
VVG3000-32	2"	2"	2"	1/2"	1/2"	2"	2"
VVG4000-32	2"	3"	3"	3/4"	3/8"	3"	3"
VVG5000-32	2"	3"	3"	3/4"	3/8"	3"	3"

