

## VVG (objem 100 až 5000 l) tlakové nádoby

- ocelové provedení, galvanizované
- vyrobené dle směrnice PED 68/2014ES
- pro stlačený vzduch a dusík
- pracovní tlak 32 bar
- pracovní teplota -20/+50 °C



Obj. č.	Objem (l)	Tlak (bar)	Rozměry (mm)			Hmotnost (kg)
			De	L	A	
VVG100-42	100	42	370	1 213	180	100
VVG200-42	200	42	446	1 587	200	150
VVG270-42	270	42	500	1 648	175	215
VVG500-42	500	42	600	2 050	155	355
VVG1000-42	1 000	42	800	2 350	145	675
VVG1500-42	1 500	42	1 000	2 305	170	1 100
VVG2000-42	2 000	42	1 100	2 490	200	1 460
VVG3000-42	3 000	42	1 200	2 990	140	1 950
VVG4000-42	4 000	42	1 450	2 790	225	2 540
VVG5000-42	5 000	42	1 450	3 390	225	2 845

### Připojení

Obj. č.	1	2	3	4	5	6	7
VVG100-42	2"	3/4"	-	3/8"	3/8"	-	3/4"
VVG200-42	2"	1"	-	1/2"	3/8"	-	1"
VVG270-42	2"	1"	1"	-	3/8"	1"	1"
VVG500-42	2"	2"	2"	1/2"	1/2"	2"	2"
VVG1000-42	2"	2"	2"	3/8"	3/8"	2"	2"
VVG1500-42	2"	2"	2"	1/2"	1/2"	2"	2"
VVG2000-42	2"	2"	2"	1/2"	1/2"	2"	2"
VVG3000-42	2"	2"	2"	1/2"	1/2"	2"	2"
VVG4000-42	2"	3"	3"	3/4"	3/8"	3"	3"
VVG5000-42	2"	3"	3"	3/4"	3/8"	3"	3"

