

VVA-OX (objem 500 až 5000 l) tlakové nádoby

- Provedení z uhlíkové oceli, práškově lakované, bílá barva RAL 9010
- vyrobené dle směrnice PED 68/2014EU
- pro kyslík (skupina 1 – vyjma vodíku a vody)
- pracovní tlak 11/12 bar
- pracovní teplota -20/+50 °C, pro objem od 1000 litrů -20/+80 °C



Obj. č.	Objem (l)	Tlak (bar)	Rozměry (mm)			Hmotnost (kg)
			De	L	A	
VVA500-11-OX	500	11	600	2 050	155	116
VVA1000-12-OX	1 000	12	800	2 350	145	210
VVA1500-12-OX	1 500	12	1 000	2 305	170	320
VVA2000-12-OX	2 000	12	1 000	2 490	200	388
VVA3000-12-OX	4 000	12	1 450	2 990	140	594
VVA4000-12-OX	3 000	12	1 450	2 790	225	835
VVA5000-12-OX	5 000	12	1 450	3 390	225	962

Připojení

Obj. č.	1	2	3	4	5	6	7
VVA500-11-OX	2"	2"	2"	-	3/8"	2"	2"
VVA1000-12-OX	2"	2"	2"	3/8"	3/8"	2"	2"
VVA1500-12-OX	2"	2"	2"	3/8"	3/8"	2"	2"
VVA2000-12-OX	2"	2"	2"	1/2"	1/2"	2"	2"
VVA3000-12-OX	2"	2"	2"	1/2"	1/2"	2"	2"
VVA4000-12-OX	2"	3"	3"	3/4"	3/8"	-	3"
VVA5000-12-OX	2"	2"	2"	1/2"	1/2"	-	3"

