

VVG-G1 (objem 1000 až 3000 l) tlakové nádoby

- ocelové provedení, oboustranně galvanizované
- vyrobené dle směrnice PED 68/2014ES
- pro stlačený vzduch a dusík
- pracovní tlak 12/16 bar
- pracovní teplota -20/+80 °C



Obj. č.	Objem (l)	Tlak (bar)	Rozměry (mm)			Hmotnost (kg)
			De	L	A	
VVG1000-12-G1	1 000	12	800	2 350	145	214
VVG1500-12-G1	1 500	12	1 000	2 305	170	325
VVG2000-12-G1	2 000	12	1 100	2 490	200	394
VVG3000-12-G1	3 000	12	1 200	2 990	140	600
VVG1000-16-G1	1 000	16	800	2 350	145	249
VVG1500-16-G1	1 500	16	1 000	2 305	170	428
VVG2000-16-G1	2 000	16	1 000	2 490	200	455
VVG3000-16-G1	3 000	16	1 200	2 990	140	635

Připojení

Obj. č.	1	2	3	4	5	6	7
VVG1000-12-G1	2"	2"	2"	3/8"	3/8"	2"	2"
VVG1500-12-G1	2"	2"	2"	1/2"	1/2"	2"	2"
VVG2000-12-G1	2"	2"	2"	1/2"	1/2"	2"	2"
VVG3000-12-G1	2"	2"	2"	1/2"	1/2"	2"	2"
VVG1000-16-G1	2"	2"	2"	3/8"	3/8"	2"	2"
VVG1500-16-G1	2"	2"	2"	1/2"	1/2"	2"	2"
VVG2000-16-G1	2"	2"	2"	1/2"	1/2"	2"	2"
VVG3000-16-G1	2"	2"	2"	1/2"	1/2"	2"	2"

