


Micro Quick Connect Couplings

Series ESMCE double shut-off

DN 2.7

Plug Profile (original size)



- One-hand quick connect couplings with smallest dimensions made of stainless steel 1.4305 (on request in stainless steel 1.4404)
- Double shut-off to avoid leaking media when disconnecting
- Please note: Valve construction designed for media flow from coupling to plug
- Suitable for low vacuum at low couple force compared to all other compatible products
- Attention: Couplings can be connected with straight-through plugs DN 2.7. However, double shut-off plugs cannot be connected with standard couplings DN 2.7
- Several fields of application, above all for liquid media in pharmacy, medical technology, chemical industry, food industry, clean-room applications, for sophisticated measure, control and regulation technology or increased hygienic requirements

Materials

- Body, sleeve, valve body, valve, plug: Stainless Steel 1.4305
- Springs, retaining ring: Stainless Steel 1.4310
- Balls: Stainless Steel 1.3541
- Seals: FKM (EPDM or FFKM on request)

Max. Working Pressure	Temperature	DN	Thread	Flow Rate	Operation	Type of valve	Media	Area	
PN 35 bar	-15°C – +200°C*	2.7	ISO 228 / DIN 13	150 l/min	One-hand	Double shut-off	Different	Europe	Coupl. 1/ Plug 5

Couplings with male thread

Thread connection	L	SW	D	L1	Weight	Type No.
M 5 m	26	9	10.5	5	9	ESMCE 5 AAB
G 1/8 m	28	11	10.5	7	12	ESMCE 18 AAB

Couplings with female thread

Thread connection	L	SW	D	L1	Weight	Type No.
M 5 f	25	9	10.5	5	10	ESMCE 5 IAB
G 1/8 f	28	12	10.5	7	14	ESMCE 18 IAB

Couplings with hose stem

Hose connection	L	D	L1	Weight	Type No.
Hose i.D. 3	34.5	10.5	13	9	ESMCE 3 TAB
Hose i.D. 4	34.5	10.5	13	10	ESMCE 4 TAB
Hose i.D. 5	34.5	10.5	13	10	ESMCE 5 TAB

For hose clips type HSE (© page 357)

Couplings with hose squeeze nut

Hose connection	L	SW	D	Weight	Type No.
Hose 3x4	34	9	10.5	15	ESMCE 34 TQAB
Hose 3x5	34	9	10.5	15	ESMCE 3 TQAB
Hose 4x6	34	9	10.5	15	ESMCE 4 TQAB

Couplings with hose squeeze nut and bulkhead screwing



Hose connection	L	SW	D	L1	SW1	G	Weight	Type No.
Hose 3x4	45	12	10.5	17	11	M 7x0.5 m	26	ESMCE 34 TQSVAB
Hose 3x5	45	12	10.5	17	11	M 7x0.5 m	26	ESMCE 35 TQSVAB
Hose 4x6	45	12	10.5	17	12	M 8x0.5 m	26	ESMCE 4 TQSVAB

Couplings with hose stem and bulkhead screwing

Hose connection	L	SW	D	L1	L2	SW1	G	Weight	Type No.
Hose i.D. 3	51	12	10.5	13	17	11	M 7x0.5 m	24	ESMCE 3 TSVAB
Hose i.D. 4	51	12	10.5	13	17	11	M 7x0.5 m	24	ESMCE 4 TSVAB
Hose i.D. 5	51	12	10.5	13	17	12	M 8x0.5 m	24	ESMCE 5 TSVAB

For hose clips type HSE (© page 357)

*subject to media and sealing material




Micro Quick Connect Couplings

double shut-off **Series ESMCE**

DN 2.7

Plug Profile (original size)



Plugs with male thread

Thread connection	L	SW	L1	L2	Weight	Type No.
M 5 m	28	9	5	10	10	ESMCE 5 NAAB
G 1/8 m	30	11	7	10	12	ESMCE 18 NAAB

Plugs with female thread

Thread connection	L	SW	L1	L2	Weight	Type No.
M 5 f	26.5	9	5	10	11	ESMCE 5 NIAB
G 1/8 f	30	12	7	10	14	ESMCE 18 NIAB

Plugs with hose stem

Hose connection	L	D	L1	L2	Weight	Type No.
Hose i.D. 3	36.5	9	13	10	9	ESMCE 3 SAB
Hose i.D. 4	36.5	9	13	10	10	ESMCE 4 SAB
Hose i.D. 5	36.5	9	13	10	10	ESMCE 5 SAB

For hose clips type HSE (© page 357)

Plugs with hose squeeze nut

Hose connection	L	SW	L1	Weight	Type No.
Hose 3x4	36	9	10	10	ESMCE 34 SQAB
Hose 3x5	36	9	10	10	ESMCE 3 SQAB
Hose 4x6	36	9	10	11	ESMCE 4 SQAB

Plugs with hose squeeze nut and bulkhead screwing

Hose connection	L	SW	L1	L2	SW1	G	Weight	Type No.
Hose 3x4	47	12	17	10	11	M 7x0.5 m	13	ESMCE 34 SQSVAB
Hose 3x5	47	12	17	10	11	M 7x0.5 m	13	ESMCE 35 SQSVAB
Hose 4x6	47	12	17	10	12	M 8x0.5 m	17	ESMCE 4 SQSVAB

Plugs with hose stem and bulkhead screwing

Hose connection	L	SW	L1	L2	L3	SW1	G	Weight	Type No.
Hose i.D. 3	53	12	13	17	10	11	M 7x0.5 m	14	ESMCE 3 SSVAB
Hose i.D. 4	53	12	13	17	10	11	M 7x0.5 m	14	ESMCE 4 SSVAB
Hose i.D. 5	53	12	13	17	10	12	M 8x0.5 m	16	ESMCE 5 SSVAB

For hose clips type HSE (© page 357)

