



Drosselfreie Winkel-Schwenk-Verschraubungen

Bestellzeichen: SB

Einschraubgewinde:
Whitworth-Rohrgewinde, zylindrisch

Zugehörige Einschraubblätter Kap. I

Choke-free banjo couplings

order code: SB

Thread:
B.S.P., parallel

Internal screw threads, see chap. I

Raccords Banjo à passage intégral

Référence de commande: SB

Filetage:
Whitworth, cylindrique

Voir taraudages correspondants chap. I

Rohr AD pipe OD Tube Ø ext.	PB Reihe series Série	S ₁	S ₂	S ₃	L ₂	I ₃	I ₂	L ₃	d ₃	i	G	kg für % ST kg for % pc. kg en %	Bestellzeichen order code Réf. cde
6	L 250	14	18	6	27	12	12,5	24	14	8	G 1/8" A	5,9	SB 6-RL
8		17	22	8	29	16	14,5	30	18	12	G 1/4" A	10,5	SB 8-RL
10		19	22	8	30	16	15,5	30	18	12	G 1/4" A	11,3	SB 10-RL
12		22	27	10	33	18	18	37	22	12	G 3/8" A	18,0	SB 12-RL
15		27	32	12	37	21	22	42	26	14	G 1/2" A	24,7	SB 15-RL
18	L 100	32	36	12	38	23	21,5	46	26	14	G 1/2" A	26,9	SB 18-RL
22		36	46	17	45	28	28,5	58	32	16	G 3/4" A	54,6	SB 22-RL
28		41	50	22	48	30,5	31,5	64	39	18	G 1" A	83,0	SB 28-RL
35		50	60	27	57	36	35,5	76	49	20	G 1 1/4" A	117,3	SB 35-RL
42		60	70	32	63	41	40	85	55	22	G 1 1/2" A	224,4	SB 42-RL
6	S 400*	17	22	8	31	16	16,5	30	18	12	G 1/4" A	10,9	SB 6-RS
8		19	22	8	31	16	16,5	30	18	12	G 1/4" A	11,4	SB 8-RS
10		22	27	10	35	18	18,5	37	22	12	G 3/8" A	19,0	SB 10-RS
12		24	27	10	35	18	18,5	37	22	12	G 3/8" A	19,6	SB 12-RS
14		27	32	12	41	21	23	42	26	14	G 1/2" A	29,7	SB 14-RS
16	250*	30	36	12	41	23	22,5	46	26	14	G 1/2" A	30,7	SB 16-RS
20		36	46	17	49	28	27,5	58	32	16	G 3/4" A	75,3	SB 20-RS
25		46	50	22	55	30,5	31	64	39	18	G 1" A	101,9	SB 25-RS
30		50	60	27	63	36	36,5	76	49	20	G 1 1/4" A	158,0	SB 30-RS
38		60	70	32	72	41	41	85	55	22	G 1 1/2" A	243,2	SB 38-RS

* Sicherheit mind. 1,6 / Security factor min. 1,6 / Facteur de sécurité min. 1,6

Hinweise zu Druck- und Temperaturangaben siehe Seiten I/9 + I/10 / Hints concerning pressure-information - see I/9 + I/10 / Informations sur les pressions - voir I/9 + I/10
L₂ = ungefährlänge bei angezogener Mutter / L₂ = approximate length with nut tightened / L₂ = longueur approximative, l'écrou étant bloqué