



## Gerade Aufschraub- Verschraubungen

Bestellzeichen: Al

Whitworth-Rohrgewinde,  
zylindrisch

## Female stud couplings

Order code: Al

B.S.P., parallel

## Unions femelles

Référence de commande: Al

Whitworth, cylindrique

Rohr AD pipe OD Tube Ø ext.	PB Reihe series Série	d <sub>5</sub>	L <sub>5</sub>	l <sub>5</sub>	t <sub>2</sub>	S	S <sub>1</sub>	G	kg für % St. kg for % pc. kg en %	Bestellzeichen order code Réf. cde
6	L 315 [863]	4	34	19	12	14	14	G 1/8"	2,5	Al 6-L/R 1/8"
8		6	39	24	17	19	17	G 1/4"	4,5	Al 8-L/R 1/4"
10		8	40	25	17	19	19	G 1/4"	5,5	Al 10-L/R 1/4"
12		10	41	26	17	24	22	G 3/8"	9,0	Al 12-L/R 3/8"
15		12	46	31	20	27	27	G 1/2"	13,0	Al 15-L/R 1/2"
18		15	47	30,5	20	27	32	G 1/2"	15,0	Al 18-L/R 1/2"
22	160 [400]	19	52	35,5	22	36	36	G 3/4"	25,5	Al 22-L/R 3/4"
28		24	55	38	24,5	41	41	G 1"	30,0	Al 28-L/R 1"
35		30	63	41	26,5	55	50	G 1 1/4"	42,0	Al 35-L/R 1 1/4"
42		36	65	42,5	28,5	60	60	G 1 1/2"	60,5	Al 42-L/R 1 1/2"
6	S 630 [1575]	4	41	26	17	19	17	G 1/4"	6,0	Al 6-S/R 1/4"
8		5	41	26	17	19	19	G 1/4"	6,5	Al 8-S/R 1/4"
10		7	43	26,5	17	24	22	G 3/8"	9,0	Al 10-S/R 3/8"
12		8	43	26,5	17	24	24	G 3/8"	10,5	Al 12-S/R 3/8"
14		10	50	32	20	27	27	G 1/2"	13,0	Al 14-S/R 1/2"
16		12	50	31,5	20	27	30	G 1/2"	16,0	Al 16-S/R 1/2"
20	400 [1000]	16	56	34,5	22	36	36	G 3/4"	26,0	Al 20-S/R 3/4"
25		20	62	37,5	24,5	41	46	G 1"	40,0	Al 25-S/R 1"
30		25	69	42	26,5	55	50	G 1 1/4"	72,0	Al 30-S/R 1 1/4"
38		32	74	43,5	28,5	60	60	G 1 1/2"	85,5	Al 38-S/R 1 1/2"